

LongLife Xtreme sealed

d	D	B	C	C0	Limiting Speed [rpm]	Ball Grade [ISO3290: 20010]	Designation
[mm]			[kN]				
6	19	6	2,34	0,95	24000	3	Xtreme 006 626-2RS/CSB
7	19	6	2,34	0,95	24000	3	Xtreme 007 607-2RS/CSB
7	22	7	3,45	1,37	22000	3	Xtreme 007 627-2RS/CSB
8	22	7	3,45	1,37	22000	3	Xtreme 008 608-2RS/CSB
10	26	8	4,75	1,96	19000	3	Xtreme 010 6000-2RS/CSB
10	30	9	5,40	2,36	17000	3	Xtreme 010 6200-2RS/CSB
10	35	11	8,52	3,4	15000	5	Xtreme 010 6300-2RS/CSB
12	28	8	5,40	2,36	17000	3	Xtreme 012 6001-2RS/CSB
12	32	10	7,28	3,1	15000	3	Xtreme 012 6201-2RS/CSB
12	37	12	10,10	4,15	14000	5	Xtreme 012 6301-2RS/CSB
15	32	9	5,85	2,85	14000	3	Xtreme 015 6002-2RS/CSB
15	35	11	8,06	3,75	13000	3	Xtreme 015 6202-2RS/CSB
15	42	13	11,90	5,4	12000	5	Xtreme 015 6302-2RS/CSB
17	35	10	6,37	3,25	13000	3	Xtreme 017 6003-2RS/CSB
17	40	12	9,95	4,75	12000	3	Xtreme 017 6203-2RS/CSB
17	47	14	14,30	6,55	11000	5	Xtreme 017 6303-2RS/CSB
20	42	12	9,95	5	11000	3	Xtreme 020 6004-2RS/CSB
20	47	14	13,5	6,55	10000	3	Xtreme 020 6204-2RS/CSB
20	52	15	16,8	7,8	9500	5	Xtreme 020 6304-2RS/CSB
25	47	12	11,9	6,55	9500	3	Xtreme 025 6005-2RS/CSB
25	52	15	14,8	7,8	8500	3	Xtreme 025 6205-2RS/CSB
25	62	17	23,4	11,6	7500	5	Xtreme 025 6305-2RS/CSB
30	55	13	13,8	8,3	8000	3	Xtreme 030 6006-2RS/CSB
30	62	16	20,3	11,2	7500	3	Xtreme 030 6206-2RS/CSB
30	72	19	29,6	16	6300	5	Xtreme 030 6306-2RS/CSB
35	62	14	16,8	10,25	7000	3	Xtreme 035 6007-2RS/CSB
35	72	17	27,0	15,3	6300	5	Xtreme 035 6207-2RS/CSB
35	80	21	35,1	19	6000	5	Xtreme 035 6307-2RS/CSB
40	68	15	17,8	11	6300	3	Xtreme 040 6008-2RS/CSB
40	80	18	32,5	19	5600	5	Xtreme 040 6208-2RS/CSB
40	90	23	42,3	24	5000	5	Xtreme 040 6308-2RS/CSB
45	75	23	20,8	14,6	5600	5	Xtreme 045 6009-2RS/CSB
45	85	19	35,1	21,6	5000	5	Xtreme 045 6209-2RS/CSB
45	100	25	55,3	31,5	4500	5	Xtreme 045 6309-2RS/CSB
50	80	16	22,9	15,6	5000	5	Xtreme 050 6010-2RS/CSB
50	90	20	37,1	23,2	4800	5	Xtreme 050 6210-2RS/CSB
50	110	27	65,0	38	4300	5	Xtreme 050 6310-2RS/CSB
55	90	18	29,6	21,2	4500	5	Xtreme 055 6011-2RS/CSB
55	100	21	46,2	29	4300	5	Xtreme 055 6211-2RS/CSB
55	120	29	74,1	45	3800	5	Xtreme 055 6311-2RS/CSB
60	95	18	30,7	23,2	4300	5	Xtreme 060 6012-2RS/CSB
60	110	22	55,3	36	4000	5	Xtreme 060 6212-2RS/CSB
60	130	31	85,2	52	3400	5	Xtreme 060 6312-2RS/CSB
65	100	18	31,9	25	4000	5	Xtreme 065 6013-2RS/CSB

d	D	B	C	C0	Limiting Speed [rpm]	Ball Grade [ISO3290: 20010]	Designation
[mm]			[kN]				
65	120	23	58,5	40,5	3600	5	Xtreme 065 6213-2RS/CSB
65	140	33	97,5	60	3200	5	Xtreme 065 6313-2RS/CSB
70	110	20	39,7	31	3600	5	Xtreme 070 6014-2RS/CSB
70	125	24	63,7	45	3400	5	Xtreme 070 6214-2RS/CSB
70	150	35	111	68	3000	5	Xtreme 070 6314-2RS/CSB
75	115	20	41,6	33,5	3400	5	Xtreme 075 6015-2RS/CSB
75	130	25	68,9	49	3200	5	Xtreme 075 6215-2RS/CSB
75	160	37	119	76,5	2800	5	Xtreme 075 6315-2RS/CSB
80	125	22	49	40	3200	5	Xtreme 080 6016-2RS/CSB
80	140	26	73	55	3000	5	Xtreme 080 6216-2RS/CSB
80	170	39	130	86,5	2600	5	Xtreme 080 6316-2RS/CSB
85	130	22	52	43	3000	5	Xtreme 085 6017-2RS/CSB
85	150	28	87,1	64	2800	5	Xtreme 085 6217-2RS/CSB
85	180	41	140	96,5	2400	16	Xtreme 085 6317-2RS/CSB
90	140	24	60,5	50	2800	5	Xtreme 090 6018-2RS/CSB
90	160	30	101	73,5	2600	5	Xtreme 090 6218-2RS/CSB
90	190	43	151	108	2400	16	Xtreme 090 6318-2RS/CSB
95	145	24	63,7	54	2800	5	Xtreme 095 6019-2RS/CSB
95	170	32	114	81,5	2400	5	Xtreme 095 6219-2RS/CSB
95	200	45	159	118	2200	16	Xtreme 095 6319-2RS/CSB
100	150	24	63,7	54	2600	5	Xtreme 100 6020-2RS/CSB
100	180	34	127	93	2400	5	Xtreme 100 6220-2RS/CSB
100	215	47	174	140	2000	16	Xtreme 100 6320-2RS/CSB
105	160	26	76,1	65,5	2400	5	Xtreme 105 6021-2RS/CSB
105	190	36	140	104	2200	5	Xtreme 105 6221-2RS/CSB
105	225	49	182	153	1800	20	Xtreme 105 6321-2RS/CSB
110	170	28	85,2	73,5	2400	5	Xtreme 110 6022-2RS/CSB
110	200	38	151	118	2000	16	Xtreme 110 6222-2RS/CSB
110	240	50	203	180	1800	20	Xtreme 110 6322-2RS/CSB
120	180	28	88,4	80	2200	5	Xtreme 120 6024-2RS/CSB
120	215	40	146	118	1900	16	Xtreme 120 6224-2RS/CSB
120	260	55	208	186	1700	20	Xtreme 120 6324-2RS/CSB
130	200	33	112	100	2000	5	Xtreme 130 6026-2RS/CSB
130	230	40	156	132	1800	16	Xtreme 130 6226-2RS/CSB
140	210	33	111	108	1800	5	Xtreme 140 6028-2RS/CSB
150	225	35	125	125	1700	5	Xtreme 150 6030-2RS/CSB
160	240	38	143	143	1600	5	Xtreme 160 6032-2RS/CSB

LongLife Xtreme open

d	D	B	C	C0	Limiting Speed [rpm]	Ball Grade [ISO3290: 20010]	Designation
[mm]			[kN]				
5	16	5	1,14	0,38	70000	3	Xtreme 005 625/CSB
6	19	6	2,34	0,95	60000	3	Xtreme 006 626/CSB
7	19	6	2,34	0,95	60000	3	Xtreme 007 607/CSB
7	22	7	3,45	1,37	53000	3	Xtreme 007 627/CSB
8	22	7	3,45	1,37	53000	3	Xtreme 008 608/CSB
10	26	8	4,75	1,96	45000	3	Xtreme 010 6000/CSB
10	30	9	5,40	2,36	43000	3	Xtreme 010 6200/CSB
10	35	11	8,52	3,4	39000	5	Xtreme 010 6300/CSB
12	28	8	5,40	2,36	43000	3	Xtreme 012 6001/CSB
12	32	10	7,28	3,1	38000	3	Xtreme 012 6201/CSB
12	37	12	10,10	4,15	33000	5	Xtreme 012 6301/CSB
15	32	9	5,85	2,85	36000	3	Xtreme 015 6002/CSB
15	35	11	8,06	3,75	32000	3	Xtreme 015 6202/CSB
15	42	13	11,90	5,4	28000	5	Xtreme 015 6302/CSB
17	35	10	6,37	3,25	32000	3	Xtreme 017 6003/CSB
17	40	12	9,95	4,75	28000	3	Xtreme 017 6203/CSB
17	47	14	14,30	6,5	26000	5	Xtreme 017 6303/CSB
20	42	12	9,95	5	26000	3	Xtreme 020 6004/CSB
20	47	14	13,5	6,55	24000	3	Xtreme 020 6204/CSB
20	52	15	16,8	7,8	23000	5	Xtreme 020 6304/CSB
25	47	12	11,9	6,55	22000	3	Xtreme 025 6005/CSB
25	52	15	14,8	7,8	22000	3	Xtreme 025 6205/CSB
25	62	17	23,4	11,6	20000	5	Xtreme 025 6305/CSB
30	55	13	13,8	8,3	19000	3	Xtreme 030 6006/CSB
30	62	16	20,3	11,2	18000	3	Xtreme 030 6206/CSB
30	72	19	29,6	16	17000	5	Xtreme 030 6306/CSB
35	62	14	16,8	10,25	17000	3	Xtreme 035 6007/CSB
35	72	17	27,0	15,3	15000	5	Xtreme 035 6207/CSB
35	80	21	35,1	19	16000	5	Xtreme 035 6307/CSB
40	68	15	17,8	11	15000	3	Xtreme 040 6008/CSB
40	80	18	32,5	19	14000	5	Xtreme 040 6208/CSB
40	90	23	42,3	24	13000	5	Xtreme 040 6308/CSB
45	75	16	22,1	14,6	16000	5	Xtreme 045 6009/CSB
45	85	19	35,1	21,6	13000	5	Xtreme 045 6209/CSB
45	100	25	55,3	31,5	12000	5	Xtreme 045 6309/CSB
50	80	16	22,9	16	15000	5	Xtreme 050 6010/CSB
50	90	20	37,1	23,2	12000	5	Xtreme 050 6210/CSB
50	110	27	65,0	38	10000	5	Xtreme 050 6310/CSB
55	90	18	29,6	21,2	14000	5	Xtreme 055 6011/CSB
55	100	21	46,2	29	10000	5	Xtreme 055 6211/CSB
55	120	29	74,1	45	9000	5	Xtreme 055 6311/CSB
60	95	18	30,7	23,2	11000	5	Xtreme 060 6012/CSB
60	110	22	55,3	36	9500	5	Xtreme 060 6212/CSB
60	130	31	85,2	52	8500	5	Xtreme 060 6312/CSB

d	D	B	C	C0	Limiting Speed [rpm]	Ball Grade [ISO3290: 20010]	Designation
[mm]			[kN]				
65	100	18	31,9	25	10500	5	Xtreme 065 6013/CSB
65	120	23	58,5	40,5	8500	5	Xtreme 065 6213/CSB
65	140	33	97,5	60	8000	5	Xtreme 065 6313/CSB
70	110	20	39,7	31	9400	5	Xtreme 070 6014/CSB
70	125	24	63,7	45	8500	5	Xtreme 070 6214/CSB
70	150	35	111	68	7500	5	Xtreme 070 6314/CSB
75	115	20	41,6	33,5	9000	5	Xtreme 075 6015/CSB
75	130	25	68,9	49	8000	5	Xtreme 075 6215/CSB
75	160	37	119	76,5	6700	5	Xtreme 075 6315/CSB
80	125	22	49	40	8200	5	Xtreme 080 6016/CSB
80	140	26	73	55	7000	5	Xtreme 080 6216/CSB
80	170	39	130	86,5	6300	5	Xtreme 080 6316/CSB
85	130	22	52	43	6700	5	Xtreme 085 6017/CSB
85	150	28	87,1	64	6700	5	Xtreme 085 6217/CSB
85	180	41	140	96,5	6000	16	Xtreme 085 6317/CSB
90	140	24	60,5	50	6300	5	Xtreme 090 6018/CSB
90	160	30	101	73,5	6300	5	Xtreme 090 6218/CSB
90	190	43	151	108	5600	16	Xtreme 090 6318/CSB
95	145	24	63,7	54	6000	5	Xtreme 095 6019/CSB
95	170	32	114	81,5	6000	5	Xtreme 095 6219/CSB
95	200	45	159	118	5300	16	Xtreme 095 6319/CSB
100	150	24	63,7	54	5600	5	Xtreme 100 6020/CSB
100	180	34	127	93	5600	5	Xtreme 100 6220/CSB
100	215	47	174	140	5000	16	Xtreme 100 6320/CSB
105	160	26	76,1	65,5	5300	5	Xtreme 105 6021/CSB
105	190	36	140	104	2200	5	Xtreme 105 6221/CSB
105	225	49	182	153	1800	20	Xtreme 105 6321/CSB
110	170	28	85,2	73,5	5000	5	Xtreme 110 6022/CSB
110	200	38	151	118	4300	16	Xtreme 110 6222/CSB
110	240	50	203	180	1800	20	Xtreme 110 6322/CSB
120	180	28	88,4	80	4800	5	Xtreme 120 6024/CSB
120	215	40	146	118	4000	16	Xtreme 120 6224/CSB
120	260	55	208	186	1700	20	Xtreme 120 6324/CSB
130	200	33	112	100	4300	5	Xtreme 130 6026/CSB
130	230	40	156	132	1800	16	Xtreme 130 6226/CSB
140	210	33	111	108	4000	5	Xtreme 140 6028/CSB
140	300	62	252	245	3600	20	Xtreme 140 6328/CSB
150	225	35	125	125	1700	5	Xtreme 150 6030/CSB
150	320	65	280	290	3200	20	Xtreme 150 6330/CSB
160	240	38	143	143	1600	5	Xtreme 160 6032/CSB
160	340	68	300	325	2800	20	Xtreme 160 6332/CSB
170	360	72	327	367	2800	20	Xtreme 170 6334/CSB
180	380	75	354	412	2800	20	Xtreme 180 6336/CSB
190	400	78	370	440	2500	20	Xtreme 190 6338/CSB