

| Ordering information | MAG W | 300 iP(L) | 400 iP(L) | 600 iP(L) | 700 iP(L) |
|---|---------|-------------|-------------|-------------|-------------|
| MAGiINTEGRA with 9 pin 24V PLC ³⁾ | # 1) 2) | | | | |
| ISO-K | iP | 410300V0505 | 410400V0505 | 410600V0505 | 410700V0505 |
| | iPL | auf Anfrage | auf Anfrage | 410600V0705 | auf Anfrage |
| CF | iP | 410300V0506 | 410400V0506 | 410600V0506 | 410700V0506 |
| | iPL | auf Anfrage | auf Anfrage | auf Anfrage | auf Anfrage |
| | | | | | |
| | MAG W | 1300 iP(L) | 1600 iP(L) | 1700 iP(L) | 2200 iP(L) |
| MAGiINTEGRA with Profibus interface ³⁾ | # 1) 2) | | | | |
| ISO-F | iP | 411300V0504 | 411600V0504 | 411700V0504 | 412200V0504 |
| | iPL | 411300V0704 | 411600V0704 | 411700V0704 | 412200V0704 |
| CF | iP | 411300V0506 | --- | 411700V0506 | 412200V0506 |
| | iPL | 411300V0706 | --- | 411700V0706 | 412200V0706 |
| MAGiINTEGRA with 9 pin 24V PLC ³⁾ | | | | | |
| ISO-F | iP | 411300V0514 | 411600V0514 | 411700V0514 | 412200V0514 |
| | iPL | 411300V0714 | 411600V0714 | 411700V0714 | 412200V0714 |
| CF | iP | 411300V0516 | --- | 411700V0516 | 412200V0516 |
| | iPL | 411300V0716 | --- | 411700V0716 | 412200V0716 |

¹⁾ IP: flanking controller installation

²⁾ IPL: bottom controller installation

³⁾ Additional interface options, including RS485 and Ethernet, are available on request

BICOM 20126-*** Printed in Germany on chlorine-free bleached paper

175.56.01

TURBOVAC MAGiINTEGRA

Magnetically levitated wide range Turbomolecular pumps



TURBOVAC MAGiNTegra

Compact product range for industrial applications

Our TURBOVAC MAGiNTegra combines

accuracy, precision and reliability - qualities that are essential to the vacuum technology and aircraft industries alike.

When it comes to vacuum technology, magnetically levitated turbomolecular pumps from Leybold feature high pumping and gas throughput for faster pumpdown to improve equipment cycle times. The new 5-axis active magnetic bearing and drive system combines high reliability and efficient operation.



ADVANTAGES Of magnetically levitated turbomolecular pumps

- Insensitivity to process particles/dust
- Shock venting tolerance
- Reliability in industrial environments
- Robust and trouble-free operation
- Low cost of ownership
- Suitability for vibration-sensitive applications
- Maintenance-free operation in most applications
- Monitoring of performance data
- Self-protection in case of exceeding operation limits or malfunction



Highlights

- Fully integrated converter and power supply eliminate the need for a conventional rack-mounted controller and interconnecting cables
- Flexible design with controller position on the side or bottom for easy system integration
- Innovative and modular industrial communication solution allows easy integration with customer equipment to meet current and future requirements
- High robustness in industrial environment due to protective class IP 54 required in PVD, display, solar and optical coating applications

Accessories

Choose from a wide range of accessories to control and monitor performance of the TURBOVAC MAGiNTegra:


- Controllers for pressure measurement
- Systems for active and passive sensors, water and air cooling facilities, venting valves, cables, etc.
- Forevacuum pumps and systems, engineering and application support

Options

MAG W Turbomolecular pumps are available with these following features:

- Inlet flanges ISO-K, ISO-F, CF
- Mounting position of the integrated controller and power supply flanking: iP version / bottom: iPL version
- Interfaces 9 pin 24V PLC, Profibus, RS485, Ethernet and others based on the customer's particular needs.

Performance Data



Applications

Coatings

- Industrial glass coating
- Web
- Optical

Solar

- Sputtering (TCO)

Display

- Flat Panel
- PVD
- LCD

Analytics

- Analytical systems
- Electron microscopes
- Particle accelerators

